

JLG 660SJ



Dimensions

Platform Size	36 x 96" / 0.91 x 2.44 m
Overall Width	7' 11" / 2.41 m
Tailswing	3' 9" / 1.14 m
Stowed Height	8' 5" / 2.57 m
Stowed Length	33' 6" / 10.21 m
Wheelbase	8' 1" / 2.46 m
Ground Clearance	12" / 30 cm
Weight*	27,600 lb / 12,519 kg
Max. Ground Bearing Pressure**	75 psi / 5.27 kg/cm²

Power Source

Dual Fuel Engine	GM Vortec 3000 MPFI, 82 hp / 61 kW
Diesel Engine	Deutz D2011L04 49 hp/36.5 kW - Caterpillar 3044C, 63.3 hp / 47.2 kW
Fuel Tank Capacity	40 gal. / 151.42 L
Hydraulic Reservoir	32 gal. / 121.13 L
Auxiliary Power	12V DC
Noise Level	70 dBa @ 7 meters

Chassis

Drive Speed 2WD/4WD	4.25 mph / 6.8 kmph
Gradeability 2WD	30%
Gradeability 4WD	45%
Turning Radius (Inside)	
Turning Radius (Inside) - 2WS	11' 4" / 3.45 m
Turning Radius (Inside) - 4WS	5' 5" / 1.65 m
Turning Radius (Outside)	
Turning Radius (Outside) - 2WS	17' 9" / 5.41 m
Turning Radius (Outside) - 4WS	11' 4" / 3.45 m

Axle Oscillation	8" / 20 cm
Tire Size	15 x 19.5
Tire Type	Lug Tread

Reach Specifications

Platform Height	66' 8" / 20.32 m
Horizontal Outreach	56' 9" / 17.3 m
Swing	360° Continuous
Platform Capacity-Restricted	n/a
Platform Capacity-Unrestricted	500 lb / 227 kg
Platform Rotator	180° Hydraulic
Jib (Range of Articulation)	6' 132° (+71, -61) / 1.83 m 132° (+71, -61)

Available Options

- **Soft Touch System 6 ft/8 ft**
- **2500W Generator**
- **36 x 72" (0.91 x 1.83 m) Platform**
- **43.5 lb (19.73 kg) Propane Tank**
- **Arctic Package - Deutz and CAT**
- **Cold Weather Start Kit**
- **Flashing Amber Beacon**
- **Hostile Environment Kit**

660SJ

